

Curing oven

Chamber furnaces with air circulation are the best solution for the final curing after the quickcoating process.

Please find below our five basic curing ovens with the following advantages:

Solid casting with heat insulation, inside made of stainless steel, high-heat output, short heating-up time, heat range of max. 300° C, controller on the front side.

Additional accessories: Controller with RS 422 interface, software, door with window, interior lighting and more ..

300° Version	HTR-060	HTR-120	HTR-240	HTR-450	HTR-1050
Liter	60	120	240	450	1050
Inside mm width/depth/height	450/380/350	650/380/500	750/550/600	750/550/1100	1200/630/1400
Outside mm width/depth/height	700/650/690	900/650/840	1000/820/940	1000/820/1440	1470/955/1920
Controller	PID	PID	PID	PID	PID
Power consumption	2,1 kW	3,1 kW	3,1 kW	6,3 kW	9,3 kW
Electrical connections	220-240 VAC 50-60 Hz 1N/PE	220-240 VAC 50-60 Hz 1N/PE	220-240 VAC 50-60 Hz 1N/PE	400 VAC 50-60 Hz 3N/PE	400 VAC 50-60 Hz 3N/PE
Air flap	Yes / 50 mm	Yes / 50 mm	Yes / 50 mm	Yes / 50 mm	Yes / 50 mm
Weight	90 kg	120 kg	165 kg	235 kg	450 kg
Accessories optional	Speed adjustment	Window	Light inside	Racks	Undercarriage

450° Version	HNA-30	HNA-60	HNA-120	HNA-250	HNA-500
Liter	30	60	120	250	500
Inside mm width/depth/height	290/420/260	350/500/350	450/600/450	600/750/600	750/1000/750
Outside mm width/depth/height	1040/1290/1385	1100/1370/1475	1200/1470/1575	1350/1650/1725	1500/1850/1800
Controller	PID	PID	PID	PID	PID
Power consumption	3,0 kW	6,0 kW	9,0 kW	12,0 kW	18,0 kW
Electrical connections	220-240 VAC 50-60 Hz 1N/PE	400 VAC 50-60 Hz 3N/PE	400 VAC 50-60 Hz 3N/PE	400 VAC 50-60 Hz 3N/PE	400 VAC 50-60 Hz 3N/PE
Weight	195 kg	240 kg	310 kg	610 kg	1030 kg
Accessories optional	Speed adjustment	Air flap	Racks	Undercarriage	

AUSPACKEN ■ made
EINSTECKEN ■ in
PRODUZIEREN ■ Germany

Wir liefern alle Öfen startbereit aus!



New!

Drawer ovens with two to nine drawers

